



TMT-R9900S

Inline Robot Soldering System



TMT-R9900S

**ESD
FREE**

**LEAD
FREE**

The Thermaltronics Robot System incorporates innovative design concepts and precision components to ensure accuracy. The combination of high precision hardware and intelligent software ensures precision soldering and low operator training costs.

- ▶ 8-Axis Soldering/Dispensing Platform
- ▶ Full vision mapping & Fiducial Marks
- ▶ Laser Height Measurement
- ▶ Curie Heat Technology provides precise temp. control
- ▶ Dynamic Compensation for board variance
- ▶ Fume extraction
- ▶ Flux & Solder Paste Dispensing (Optional)
- ▶ PCB Loader w/Preheater (Optional)
- ▶ Nitrogen Protection (Optional)
- ▶ Desoldering (Optional)

TMT-R9900S FEATURES

1. Unlike typical Cartesian robots the Thermaltronics Robot, Model TMT-R9900S, is equipped with full vision, (eyes) to verify the procedure being undertaken and does not simply follow a pre-determined program. In this respect it has an observation mode, a verification mode and as a result – a decision making capability. (Basically a brain). This capability of collecting and utilizing data for production processing is one of the most important factors necessary to meet the requirements of Industry 4.0 standards.
2. Through the use of servo motors and precision ballscrews, the Thermaltronics Robotic system is able to accurately meet the requirements of high speed operation, repeatability and durability. The software is designed to transform system commands into functional operating procedures and with its 8-axis capability, 360° independent fixture rotation, solder tip and solder wire feeding operation from separate axis control, the applications extend beyond conventional soldering and dispensing operations.
3. Application programming is made simple by using full image-merging and mapping techniques.
4. Dynamic laser height measurement/adaptive control, ensures precision soldering repeatability.
5. A full vision mapping system with fiducial marks, provides for intelligent decision making during procedural operations

THERMALTRONICS

SPEED - QUALITY - COST REDUCTION - INCREASED PRODUCTIVITY

www.thermaltronics.com

THERMALTRONICS



TMT-R9900S

Inline Robot Soldering System

TMT-R9900S SPECIFICATIONS

Input Line Voltage	TMT-R9900PS-2	220-240 VAC
Servo Motor Axis	8 Axes	
Camera View	450mm x 550mm	
PCBA Size Max	450mm x 550mm	
Soldering Region Max	450mm x 450mm with rotation	
Dynamic Range of Shaft	X Axis	550mm Standard
	Y Axis	800mm Standard
	Z1, Z2 Axis	150mm
	Q Axis	360°
Shaft Speed	X, Y Axis	0.1 ~ 1200 mm/sec
	Z Axis	0.1 ~ 800 mm/sec
	Q Axis	0.1 ~ 360°/sec
Position Repeatability	X, Y & Z Axis	±0.01 mm
	Q Axis	±0.02°
Rotation Platform	Repeatability	sec ±5 (0.001°)
	Accuracy	sec ±10 (0.002°)
	Parallelism	mm ±0.005
	Concentricity	mm ±0.01
Camera	Resolution	0.015mm
	Sensor	1/2" CMOS
	Pixel Size	6.2 x 5.2 Micron
Air Pressure	Max. 8 Bar / 120 psi	
Solder wire diameter range	0.4 ~ 1.0 (mm) (Optional: 0.3mm - 2.0mm)	
Controller	Industrial Computer w/Proprietary Software	
Ports and connectors	RJ45, USB, COM	
Operating System	Windows 10 Professional	
Soldering System	120 watts (40 watts RF output)	
Curie Heat Technology	250C ~ 500C (Tip cartridge pre-defined)	
Power Supply	220 ~ 240V AC	
Power Consumption	2.2 KVA	
Dimensions	1600mm (H) x 1452mm (D) x 1000mm (W)	
Weight	750 KG	